

# 8. SE-100

## SPECIFICATIONS

Speaker ..... Electret push-pull static type 2-way system  
 Static capacity ..... 140pF (each channel, including the connecting cord)  
 Frequency response ..... 20 to 35,000 Hz  
 Sensitivity ..... 95 dB or greater (input 100V) with B&K Artificial ear 4153  
 Maximum sound pressure level ..... 115 dB  
 Distortion ..... Less than 1% (at sound pressure level 100 dB)  
 Separation ..... 40 dB or more (at audible band)  
 Connecting cord ..... 8.2 ft./2.5 m (with 4-P plug)  
 Weight ..... 13 oz/360 g (except connecting cord)

### NOTE:

Specifications and the design subject to possible modification without notice due to improvements.

## PARTS LIST

| Key No. | Description                      | Part No.  |  |
|---------|----------------------------------|-----------|--|
| 1       | Speaker Assembly (Electret type) | SXC-048-0 |  |
| 2       | Case (L)                         | SXC-041-0 |  |
| 3       | Case (R)                         | SXC-042-0 |  |
| 4       | Ear Pad                          | SXC-043-0 |  |
| 5       | 4-P Plug with Connecting Cord    | K71-643-0 |  |
| 6       | Lead Wire                        | SXC-044-0 |  |
| 7       | Holder Unit                      | SXC-045-0 |  |
| 8       | Shaft for Holder                 | SXC-046-0 |  |
| 9       | Head Band Assembly               | SXC-047-0 |  |
| 10      | Capacitor (39pF, DC 2kV)         | SCG-001-0 |  |
|         | Packing Case                     | H93-641-0 |  |
|         | Styrol Protector                 | H92-609-0 |  |
|         | Operating Guide (SE-100, JB-100) | SRB-009-0 |  |



