

5. SE-30A

SPECIFICATIONS

Matching impedance	4 to 16Ω
Frequency response	20 to 20,000 Hz
Sensitivity	115 dB/0.3V at 400 Hz (Measured with B&K's Artificial Ear Model 4153)
Input (maximum)	2V (each channel)
Speaker	2-3/4" dynamic speaker with a dome of polyester resin
Cord	Retractable coiled cord extensible up to 16.4 feet (5m), with 3-P plug
Weight	Approx. 14 oz (380 g), less cord

NOTE:

Specifications and the design subject to possible modification without notice due to improvements.

PARTS LIST

Key No.	Description	Part No.
1	Speaker Assembly	SXC-001-0
2	Protection Board (Left)	SCD-329-A
3	Protection Board (Right)	SCD-331-A
4	Case	SXC-002-0
5	Name Plate	SAL-004-0
6	Ear pad	SCD-116-B
7	Head pad	SCD-117-B
8	Head Band (A)	N63-741-A
9	Head Band (B)	N63-742-A
10	Adjusting Knob (Left & Right)	SXC-003-0
11	Coiled Cord with 3-P Plug	SXC-004-0
12	Lead Wire	SXC-005-0
13	Band Shaft	SXC-006-0
	Packing Case (not for SE-30A/up)	SHG-004-0
	Leather Case (SE-30A/up only)	SHF-001-0
	Outer Case (SE-30A/up only)	SHG-005-0
	Operating Guide	R12-787-0



